


















Technical information EIGHT

Construction: Woven vinyl flooring, product standard EN 15114

www.bolon.com for updated information

Classification:		EN 685	33
Weight: Tiles		ISO 8543	4,2 kg/m ²
Thickness: Tiles		ISO 1765	3,0 mm
Roll width:		EN 426	-
Roll length:		EN 426	-
Tile dimension:		EN 427	500 x 500 mm. 16 pcs box / 4 sqm
Castor chair:		EN 985	Continuous use
Body voltage:		ISO 1815	≤ 2,0 kV
Thermal resistance:		ISO 8302	0,02 m ² K/W* Suitable for underfloor heating
Impact sound:		EN ISO 140-8	12 dB*
Airborne sound abs.:		EN ISO 354	0,10*
Colour fastness to light:		ISO 105-B02	8
Dimension stability:		ISO 2551	-1,2%; to +0,5%
Residual indentation:		EN 433	< 0,2 mm
Reaction to fire:		EN 13501-1	B _{fl} -s1
Critical radiant flux:		ASTM D 648	Class 1
Smoke density:		ASTM D 662	≤ 450
Anti slip property/ friction:		DIN 51130 EN 13893	R9 > 0,3
CE certification:		EN 14041	No 0402-CPD-419001
Floor Score Certification:		SCSEC-10.2-2007	SCS-FS-02240 (Tiles)
Classification: Tiles		CSTB	under testing at time of printing

Registered in BASTA

* Typical value

