



# Style Specifications – Event Series

All floors shown or listed in this specification shall be Event Series by Centiva, Florence, AL, 35630.

Specific product shall be: \_\_\_ - \_\_\_ - \_\_\_ E \_\_\_ - \_\_\_ in size \_\_\_" x \_\_\_"  
Style Color Series Surface Edge

The Centiva Event Series shall be heterogeneous, resilient flooring with a .030" high density wearlayer. All products shall have an overall gauge of .120" (3 mm) nominal. See individual product specification for sizes offered in each style. The resilient tile shall be manufactured in accordance with ASTM Specification F-1700 and shall be asbestos free. All products shall have a Commercial Limited 20-year Wear Warranty and Residential Lifetime Wear Warranty. The adhesive shall be CENTI 2001 WET SET, CENTI 2000 EP, or CENTI 6000 SP. Installation shall be in accordance with the latest Centiva Installation Guidelines found at [www.centiva.com](http://www.centiva.com).

*The Event Series square tiles may be installed with one-quarter turn (tessellated) or in one direction. For best design appeal and results Centiva recommends the one-quarter turn installation method. Rectangular shaped tiles should be installed in one direction.*

## GRANITE

NS 7131-E Jura Stone      NS 7132-E Jomon Stone      NS 7133-E Coquina Stone

<b>Classification:</b>	ASTM F 1700 Class III Solid Vinyl Tile		
<b>Construction:</b>	Multiple layers with backing which contains pre- and post-consumer material		
<b>Overall Thickness:</b>	.120" / 3 mm (nominal)		
<b>Wearlayer Thickness:</b>	.030" clear, rigid high density PVC		
<b>Size:</b>	12" x 18", 18" x 18"		
<b>Edge:</b>	Square		
<b>Surface Texture:</b>	Quarry (QU)		
<b>Standard Colors:</b>	3 colors		
<b>Warranty:</b>	20 years Commercial, Lifetime Residential		
<b>Recycling:</b>	Suitable		
<b>Test Performance:</b>	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good (*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product

## LIMESTONE

NS 7106-E Sea Grass Limestone      NS 7107-E Ash Limestone      NS 7108-E Minos Limestone

<b>Classification:</b>	ASTM F 1700 Class III Solid Vinyl Tile		
<b>Construction:</b>	Multiple layers with backing which contains pre- and post-consumer material		
<b>Overall Thickness:</b>	.120" / 3 mm (nominal)		
<b>Wearlayer Thickness:</b>	.030" clear, rigid high density PVC		
<b>Size:</b>	12" x 18", 18" x 18"		
<b>Edge:</b>	Square		
<b>Surface Texture:</b>	Quarry (QU)		
<b>Standard Colors:</b>	3 colors		
<b>Warranty:</b>	20 years Commercial, Lifetime Residential		
<b>Recycling:</b>	Suitable		
<b>Test Performance:</b>	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good (*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product

## MARBLE

NS 7101-E Serenade Marble    NS 7102-E Passion Beige Marble    NS 7103-E Mario White Marble

<b>Classification:</b>	ASTM F 1700 Class III Solid Vinyl Tile		
<b>Construction:</b>	Multiple layers with backing which contains pre- and post-consumer material		
<b>Overall Thickness:</b>	.120" / 3 mm (nominal)		
<b>Wearlayer Thickness:</b>	.030" clear, rigid high density PVC		
<b>Size:</b>	12" x 18", 18" x 18"		
<b>Edge:</b>	Square		
<b>Surface Texture:</b>	Frost (FR)		
<b>Standard Colors:</b>	3 colors		
<b>Warranty:</b>	20 years Commercial, Lifetime Residential		
<b>Recycling:</b>	Suitable		
<b>Test Performance:</b>	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good (*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product

## RIVER ROCK

NS RR61-E Cortez Gold    NS RR64-E Sacred Rock    NS RR65-E Tucson Gray,  
NS RR72-E Canyon Gray    NS RR73-E Mesa Verde    NS RR74-E Pueblo,  
NS RR75-E New Coronado

<b>Classification:</b>	ASTM F 1700 Class III Solid Vinyl Tile		
<b>Construction:</b>	Multiple layers with backing which contains pre- and post-consumer material		
<b>Overall Thickness:</b>	.120" / 3 mm (nominal)		
<b>Wearlayer Thickness:</b>	.030" clear, rigid high density PVC		
<b>Size:</b>	12" x 18", 18" x 18"		
<b>Edge:</b>	Square		
<b>Surface Texture:</b>	Rock (RK)		
<b>Standard Colors:</b>	7 colors		
<b>Warranty:</b>	20 years Commercial, Lifetime Residential		
<b>Recycling:</b>	Suitable		
<b>Test Performance:</b>	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good (*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product

## SANDSTONE

NS 7110-E Pale Sandstone    NS 7112-E Cordovan Sandstone

<b>Classification:</b>	ASTM F 1700 Class III Solid Vinyl Tile		
<b>Construction:</b>	Multiple layers with backing which contains pre- and post-consumer material		
<b>Overall Thickness:</b>	.120" / 3 mm (nominal)		
<b>Wearlayer Thickness:</b>	.030" clear, rigid high density PVC		
<b>Size:</b>	12" x 18", 18" x 18"		
<b>Edge:</b>	Square		
<b>Surface Texture:</b>	Frost (FR)		
<b>Standard Colors:</b>	2 colors		
<b>Warranty:</b>	20 years Commercial, Lifetime Residential		
<b>Recycling:</b>	Suitable		
<b>Test Performance:</b>	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good (*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product

## Style Specifications – Event Series



### OKARA STONE NS 7126-E Okara Gray NS 7127-E Okara Tan

<b>Classification:</b>	ASTM F 1700 Class III Solid Vinyl Tile		
<b>Construction:</b>	Multiple layers with backing which contains pre- and post-consumer material		
<b>Overall Thickness:</b>	.120" / 3 mm (nominal)		
<b>Wearlayer Thickness:</b>	.030" clear, rigid high density PVC		
<b>Size:</b>	12" x 18", 18" x 18"		
<b>Edge:</b>	Square		
<b>Surface Texture:</b>	Frost (FR)		
<b>Standard Colors:</b>	2 colors		
<b>Warranty:</b>	20 years Commercial, Lifetime Residential		
<b>Recycling:</b>	Suitable		
<b>Test Performance:</b>	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good (*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product

### QUARTZITE NS 7230-E Swiss Quartzite NS 7231-E Mediterranean Quartzite, NS 7232-E Moroccan Quartzite NS 7233-E Rosa Quartzite

<b>Classification:</b>	ASTM F 1700 Class III Solid Vinyl Tile		
<b>Construction:</b>	Multiple layers with backing which contains pre- and post-consumer material		
<b>Overall Thickness:</b>	.120" / 3 mm (nominal)		
<b>Wearlayer Thickness:</b>	.030" clear, rigid high density PVC		
<b>Size:</b>	12" x 18", 18" x 18"		
<b>Edge:</b>	Square		
<b>Surface Texture:</b>	Quarry (QU)		
<b>Standard Colors:</b>	4 colors		
<b>Warranty:</b>	20 years Commercial, Lifetime Residential		
<b>Recycling:</b>	Suitable		
<b>Test Performance:</b>	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good (*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product

## TRAVERTINE

NS 7210-E Roman Travertine, NS 7211-E Navona Travertine,  
NS 7212-E Toscano Travertine, NS 7213-E Silver Travertine

<b>Classification:</b>	ASTM F 1700 Class III Solid Vinyl Tile		
<b>Construction:</b>	Layered tile consisting of wearlayer, film, and backing		
<b>Overall Thickness:</b>	.120" / 3 mm (nominal)		
<b>Wearlayer Thickness:</b>	.030" clear, rigid high density PVC		
<b>Size:</b>	12" x 18", 18" x 18"		
<b>Edge:</b>	Square		
<b>Surface Texture:</b>	Quarry (QU)		
<b>Standard Colors:</b>	4 colors		
<b>Warranty:</b>	20 years Commercial, Lifetime Residential		
<b>Recycling:</b>	Suitable		
<b>Test Performance:</b>	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good (*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product

## EVENT PLANK

WP OL03-E Cinnamon Olivet	WP OL05-E Allspice Olivet	WP OL07-E Nutmeg Olivet
WP 3208-E Wheat Ash	WP 3209-E Burnt Ash	WP 3241-E Natural Cherry
WP GW19-E Antique Ochre	WP GW29-E Antique Cimarron	WP GW38-E Antique Walnut
WP BB32-E Bamboo	WP 3305-E American Cherry	WP 3308-E Ash
WP 3309-E Limed Oak	WP 3307-E European Cherry	WP 3319-E Rock Maple
WP 3315-E Mahogany	WP 3317-E Golden Pine	WP 3318-E Knotty Pine
WP 3321-E American Oak	WP 3350-E Smoked Oak	WP 3352-E Harvest Oak
WP 3354-E Honey Oak		

<b>Classification:</b>	ASTM F 1700 Class III Solid Vinyl Tile		
<b>Construction:</b>	Layered plank consisting of wearlayer, film, and backing		
<b>Overall Thickness:</b>	.120" / 3 mm (nominal)		
<b>Wearlayer Thickness:</b>	.030" clear, rigid high density PVC		
<b>Size:</b>	4" x 36" or 6" x 36"		
<b>Edge:</b>	Square		
<b>Surface Textures:</b>	Frost (FR) <i>Bamboo</i> Natural Grain (NG) <i>Rock Maple, Ash, Limed Oak, American Cherry, European Cherry, Natural Cherry, Antique Walnut</i> Rustic (RU) <i>Smoked Oak, Honey Oak, Harvest Oak</i> Third Grain (TG) <i>American Oak, Mahogany, Antique Ochre, Antique Cimarron, Allspice Olivet, Cinnamon Olivet, Nutmeg Olivet</i> Weathered (WE) <i>Knotty Pine, Golden Pine, Wheat Ash, Burnt Ash</i>		
<b>Standard Colors:</b>	22 colors		
<b>Warranty:</b>	20 years Commercial, Lifetime Residential		
<b>Recycling:</b>	Suitable		
<b>Test Performance:</b>	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good (*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product