

# Evolving Styles Tile & Sheet Architectural Specification

## COMPANY INFORMATION

Flexco Corporation  
1401 East 6<sup>th</sup> Street  
Tuscumbia, AL, USA 35674  
Telephone: (256) 383-7474; (800) 633-3151  
Facsimile: (256) 381-0322; (800) 346-9075  
Email: [info@flexcofloors.com](mailto:info@flexcofloors.com), [technical@flexcofloors.com](mailto:technical@flexcofloors.com)  
Internet: [www.flexcofloors.com](http://www.flexcofloors.com)  
Sweet's Catalog: 09650/FLE; Buyline 0254; [www.sweets.com](http://www.sweets.com)

## ARCHITECTURAL SPECIFICATION

### EVOLVING STYLES TILE

FLEXCO Evolving Styles Rubber Tile manufactured by FLEXCO, Tuscumbia, AL 35674. Evolving Styles Rubber Tile shall be constructed of first-quality materials and shall be free from imperfections. Tile shall be (.100" or .125") in thickness and (12" x 12", 18" x 18", 36" x 36") in size and shall be color selected. Tiles shall be free from objectionable odors, blisters, cracks and other imperfections, which will detract from the serviceability and appearance of the tiles. Tile shall conform to ASTM F 1344, and shall contain no asbestos fiber. Install Evolving Styles Tile with recommended FLEXCO adhesives.

### EVOLVING STYLES SHEET

FLEXCO Evolving Styles Rubber Sheet manufactured by FLEXCO, Tuscumbia, AL 35674. Evolving Styles Rubber Sheet shall be constructed of first-quality materials and shall be free from imperfections. Sheet shall be (.100" or .125") in thickness and (36", 48") in width and shall be color selected. Sheet shall be free from objectionable odors, blisters, cracks and other imperfections, which will detract from the serviceability and appearance of the tiles. Tile shall conform to ASTM F 1859, and shall contain no asbestos fiber. Install Evolving Styles Sheet with recommended FLEXCO adhesives.

# specifications | evolving styles

## order prefix:

Evolving Styles®	Radial® (RLT/RBT)	Radial® II (RGT)
Gauge	1/8"	1/8"
Size	18" x 18"	18" x 18"
Pieces /Ctn	20	20
Weight /Ctn (lb)	46	46
Sq Ft /Ctn	45	45

Evolving Styles®	Radial® III (RCT)	Weave (WW)
Gauge	1/8"	1/8"
Size	18" x 18"	18" x 18"
Pieces /Ctn	20	20
Weight /Ctn (lb)	46	45
Sq Ft /Ctn	45	45

Evolving Styles®	Square² (SQ)	Hammered (SE)	
Gauge	1/8"	1/8"	.080"
Size	18" x 18"	18" x 18"	24" x 24"
Pieces /Ctn	20	20	20
Weight /Ctn (lb)	45	46	60
Sq Ft /Ctn	45	45	80

Evolving Styles®	1/8" Smooth †	.100" Smooth †
Size Tile (CE & WE)	12" x 12" 18" x 18" 36" x 36"	12" x 12" 18" x 18" 36" x 36"
Sheet* (CE & WE)	36" x 25" 48" x 25"	36" x 25" 48" x 25"
Weight/Ctn (lb)		
12" x 12"	52	56
36" x 36"	62	68
Sheet Weight (lb)	10.8/sq yd	8.5/sq yd
Sq Ft/Ctn		
12" x 12"	45	60
18" x 18"	45	56.25
36" x 36"	54	72

\* Special orders for lengths greater than 25'.

† Sheet rubber manufactured untrimmed must be double-cut on the job site.

\*\*Repel & IMO formulation not available in sheet.

Note: Add HW to color number for pre-grooved Heat Weld tiles available in 36" x 36" x 1/8" gauge.

