

Natural Elements Luxury Vinyl Stone Tile Maintenance

1. Initial Maintenance

- Allow 48 hours after installation for proper curing of the adhesives
- Remove any coverings used for floor protection after installation prior to cleaning
- Sweep, dust mop and/or vacuum floor to remove any dirt or particulates accumulated on the floor
- Clean the floor with a high quality Vinyl Floor cleaner such as Bona® Stone, Tile & Laminate Floor Cleaner or for large areas use an Auto Scrubber with White Pads and a mild solution of Neutral pH cleaner such as Spartan Chemicals Green Solutions All Purpose Cleaner or Spartan Chemicals Clean by Peroxy
- Do not use detergents, abrasive cleaners or “mop and shine” products as they will dull the look of the floor
- Do not use vacuums with a beater bar or electric brooms with hard plastic bottoms and no padding as this may cause discoloration, scratching and loss of gloss

2. Daily Maintenance

- Sweep, dust mop and/or vacuum floor to remove any dirt or particulates accumulated on the floor
- Remove any spills or other large deposits of dirt and / or debris

3. Weekly Maintenance

Keep in mind, if the appearance of the flooring becomes unacceptable; this procedure may require completion more frequently to provide acceptable appearance.

- Sweep, dust mop and/or vacuum floor to remove any dirt or particulates accumulated on the floor
- Clean the floor with a high quality Vinyl Floor cleaner such as Bona® Stone, Tile & Laminate Floor Cleaner or for large areas use an Auto Scrubber with White Pads and a mild solution of Neutral pH cleaner such as Spartan Chemicals Green Solutions All Purpose Cleaner or Spartan Chemicals Clean by Peroxy
- Do not use detergents, abrasive cleaners or “mop and shine” products as they will dull the look of the floor
- Do not use vacuums with a beater bar or electric brooms with hard plastic bottoms and no padding as this may cause discoloration, scratching and loss of gloss

4. Floor Protection Devices

- When moving in appliances or heavy furniture, it is always wise to protect the floor from scuffing and tears by using something to protect the floor
- Use floor protectors under furniture or fixtures to reduce indentation; as a rule of thumb, the heavier the item the wider the floor protection device needed
- Place walk-off mats at outside entrances manufactured with non-staining backs to prevent discoloration

COMPANY INFORMATION

Flexco Corporation

1401 East 6th Street

Tuscumbia, AL, USA 35674

Phone: (256) 383-7474; (800) 633-3151

Email: info@flexcofloors.com, installhelp@flexcofloors.com, technical@flexcofloors.com