


















# Technical information SPEKTRA

Construction: Woven vinyl flooring, product standard EN 15114

[www.bolon.com](http://www.bolon.com) for updated information

<b>Classification:</b>		EN 685	33
<b>Weight: Rolls</b>		ISO 8543	3,2 kg/m <sup>2</sup>
<b>Thickness: Rolls</b>		ISO 1765	2,5 mm
<b>Roll width:</b>		EN 426	2040 mm
<b>Roll length:</b>		EN 426	25 m
<b>Tile dimension:</b>		EN 427	-
<b>Castor chair:</b>		EN 985	Continuous use
<b>Body voltage:</b>		ISO 1815	≤ 2,0 kV
<b>Thermal resistance:</b>		ISO 8302	0,02 m <sup>2</sup> K/W* Suitable for underfloor heating
<b>Impact sound:</b>		EN ISO 140-8	12 dB*
<b>Airborne sound abs.:</b>		EN ISO 354	0,10*
<b>Colour fastness to light:</b>		ISO 105-B02	8
<b>Dimension stability:</b>		ISO 2551	-1,2%; to +0,5%
<b>Residual indentation:</b>		EN 433	< 0,2 mm
<b>Reaction to fire:</b>		EN 13501-1	B <sub>fl</sub> -s1
<b>Critical radiant flux:</b>		ASTM D 648	Class 1
<b>Smoke density:</b>		ASTM D 662	≤ 450
<b>Anti slip property/ friction:</b>		DIN 51130 EN 13893	R9 > 0,3
<b>CE certification:</b>		EN 14041	No 0402-CPD-419001
<b>Floor Score Certification:</b>		SCSEC-10.2-2007	SCS-FS-02007 (Rolls)
<b>Classification: Rolls</b>		CSTB	under testing at time of printing

\* Typical value

