

Timbersafe II

Wood-Look Slip Resistant Flooring



Altro Timbersafe II™ provides the warmth and beauty of wood, with the slip and stain resistance of Altro safety flooring. Timbersafe is ideal for environments where style, timeless elegance, comfort, durability, and safety are needed. It is ideal for busy public areas, hospital patient rooms, waiting rooms, procedure rooms, corridors, reception areas, schools, and retail facilities.

- Altro Maxis Cleaning Technology - *reduces cleaning and maintenance*
- AltroSan Integrated Bacteriostat - *inhibits growth of microorganisms and MRSA's*
- Superior Slip Resistance, Even When Wet
- Excellent Stain Resistance
- Low VOC Emissions for Improved Air Quality
- May Contribute to or Comply with LEED™ Credits
- Contains 3% Post-Consumer Recycled Content
- Does not contain DEHP
- Pattern Repeat is every 4'2"

Thickness: 0.08" (2.0mm)
Roll Length: 66' (20m)
Width: 6.7' (2.0m)
Weight: 4.8lbs/yd² (2.6kg/m²)
Warranty: 7 years
Wear Layer: .8mm including a .1mm wood visual
Format: Sheet




ASTM Standard	(Tested in accordance with ASTM tests)	
ASTM F 970	Static Load Limit	2500psi
ASTM D 2047	Slip Resistance	D 0.96
ASTM E 648	Critical Radiant Flux	Pass
ASTM E 662	Smoke Generation	Pass
ASTM F 1303/1700	Physical Properties	Pass
ASTM C 501	Taber Abrasion	Pass
CAN/ULC-S102.2	Surface Burning	Tested


Category	LEED NC&CI Credits	Description Summary
Materials and Resources	4.1 & 4.2	Contains 3% Post-Consumer Recycled Content
Indoor Environmental Air Quality	EQ 4.3 EQ 4.1	Low VOC emitting materials



Blonde Oak TS2016
WR: 225 AM: 225



Classic Oak TS2017
WR: 15 AM: 15



Fruit Wood TS2023
WR: 259 AM: 225




Golden Beech TS2019
WR: 171 AM: 246




Mellow Beech TS2020
WR: 224 AM: 224




Rich Walnut TS2024
WR: 227 AM: 227



Rustic Pine TS2021
WR: 226 AM: 226



Traditional Oak TS2018
WR: 16 AM: 258



Warm Cherry TS2022
WR: 160 AM: 160