




















Technical Information

CONSTRUCTION: Woven vinyl flooring | COLLECTION: TWILIGHT

			 Rolls ¹	 Rolls ²	 Rolls ³
Classification:	 EN 685		32	33	31
Weight:	 EN 430		3.05 kg/m ²	3.2 kg/m ²	3.05 kg/m ²
Thickness:	 EN 428		2.8 mm	2.5 mm	2.8 mm
Roll length:	 EN 426		25 m (approx 82')	25 m (approx 82')	25 m (approx 82')
Width:	 EN 426		200 cm (6'7)	200 cm (6'7)	200 cm (6'7)
Chair with castors:	 EN 985		For continuous use	For continuous use	For continuous use
Impact sound:	 ISO 140-8		ΔLw=17 dB	ΔLw=11 dB	ΔLw=17 dB
Dimension stability:	 EN 434		< 0.25%	< 0.25%	< 0.25%
Curling:	 EN 434		< 2 mm	< 2 mm	< 2 mm
Residual indentation:	 EN 433		< 0.2 mm	< 0.2 mm	< 0.2 mm
Body voltage:	 ISO 1815		< 2 kV	< 2 kV	< 2 kV
Heat flux:	 EN 12664		0.03 m ² K/W	0.01 m ² K/W	0.03 m ² K/W
Colour fastness:	 ISO 105-B02		> 6	> 6	> 6
Slip resistance:	 EN 13893		> 0.3	> 0.3	> 0.3
		DIN 51130	R9	-	R9
Fire rating:	EN 13501-1 ASTM E 648 ASTM E 662	B _{fl} -s1 Class 1 (NFPA 101) 450 or less	B _{fl} -s1 Class 1 (NFPA 101) 450 or less	B _{fl} -s1 Class 1 (NFPA 101) 450 or less	B _{fl} -s1 Class 1 (NFPA 101) 450 or less
Classification:	CSTB	U3SP3E1-2C1 NO 12/03 1346	Not Completed	Not Completed	Not Completed
Certification:	 EN 14041	No 0402-CPD-419001	No 0402-CPD-419001	No 0402-CPD-419001	No 0402-CPD-419001



BOLON AB complies with management system certification according to ISO 9001 and ISO 14001.



Bolon Flooring is recyclable

BOLON AB Box 73 | SE-523 22 Ulricehamn, Sweden
Tel: + 46 321 530 400 | Fax: + 46 321 530 450
info@bolon.se | www.bolon.com



WORLD LEADER IN WOVEN VINYL FLOORING