



Style Specifications – Victory Series

All floors shown or listed in this specification shall be Victory Series by Centiva, Florence, AL, 35630.

Specific product shall be: ___ ___ V ___ ___ in size ___" x ___"
Style Color Series Surface Edge

The Centiva Victory Series shall be homogeneous or constructed with a .032" high density wearlayer depending on product . All products shall have an overall gauge of .120" (3 mm) nominal. See individual product specification for sizes offered in each style. The resilient tile shall be manufactured in accordance with ASTM Specification F-1700, and shall be asbestos free. All products shall have a Commercial Limited 20-year Wear Warranty and Residential Lifetime Wear Warranty. The adhesive shall be CENTI 2001 WET SET, CENTI 2000 EP, or CENTI 6000 SP. Installation shall be in accordance with the latest Centiva Installation Guidelines found at www.centiva.com.

CANYON COLORS

Classification:	ASTM F 1700 Class III Solid Vinyl Tile		
Construction:	Multiple layers with backing which contains pre- and post-consumer materials		
Overall Thickness:	.120" / 3 mm (nominal)		
Wearlayer Thickness:	.032" clear, rigid high density PVC		
Size:	12" x 12", 12" x 18", 18" x 18", 12" x 36", plus additional custom sizes		
Edge:	Square, Slight Bevel		
Surface Texture:	Fresco (FC) <i>recommended</i> , Frost (FR), Pathway (PH), Quarry (QU)		
Standard Colors:	4 colors		
Warranty:	20 years Commercial, Lifetime Residential		
Recycling:	Suitable		
Test Performance:	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good ("textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product

CORAL REEF

Classification:	ASTM F 1700 Class III Solid Vinyl Tile		
Construction:	Homogeneous		
Overall Thickness:	.120" / 3 mm (nominal)		
Wearlayer Thickness:	N/A, solid vinyl tile		
Size:	12" x 12", 12" x 18", 18" x 18", 12" x 36", 18" x 36", 36" x 36" plus additional custom sizes		
Edge:	Square, Slight Bevel, Deep Bevel		
Surface Texture:	Slate (SS) <i>recommended</i> , Granite (JS)		
Standard Colors:	23 colors		
Warranty:	20 years Commercial, Lifetime Residential		
Recycling:	Suitable		
Test Performance:	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good ("textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product

C-TECH

Classification:	ASTM F 1700 Class III Solid Vinyl Tile		
Construction:	Multiple layers with backing which contains pre- and post-consumer materials		
Overall Thickness:	.120" / 3 mm (nominal)		
Wearlayer Thickness:	.032" clear, rigid high density PVC		
Size:	12" x 12", 12" x 18", 18" x 18", 12" x 36", plus additional custom sizes		
Edge:	Square, Slight Bevel		
Surface Texture:	Fresco (FC) <i>recommended</i> , Frost (FR), Pathway (PH), Quarry (QU)		
Standard Colors:	10 colors		
Warranty:	20 years Commercial, Lifetime Residential		
Recycling:	Suitable		
Test Performance:	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good (*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product

GLITTER

Classification:	ASTM F 1700 Class III Solid Vinyl Tile		
Construction:	Multiple layers with backing which contains pre- and post-consumer materials		
Overall Thickness:	.120" / 3 mm (nominal)		
Wearlayer Thickness:	.032" clear, rigid high density PVC		
Size:	12" x 12", 12" x 18", 18" x 18", 12" x 36", plus additional custom sizes		
Edge:	Square, Slight Bevel		
Surface Texture:	Frost (FR) <i>recommended</i> , Fresco (FC), Pathway (PH), Quarry (QU)		
Standard Colors:	13 colors		
Warranty:	20 years Commercial, Lifetime Residential		
Recycling:	Suitable		
Test Performance:	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good (*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product

MAGICS

Classification:	ASTM F 1700 Class III Solid Vinyl Tile		
Construction:	Homogeneous		
Overall Thickness:	.120" / 3 mm (nominal)		
Wearlayer Thickness:	N/A, solid vinyl tile		
Size:	12" x 12", 12" x 18", 18" x 18", 12" x 36", 18" x 36", 36" x 36" plus additional custom sizes		
Edge:	Square, Slight Bevel, Deep Bevel		
Surface Texture:	Slate (SS) <i>recommended</i> , Granite (JS)		
Standard Colors:	21 colors		
Warranty:	20 years Commercial, Lifetime Residential		
Recycling:	Suitable		
Test Performance:	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good (*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product

Style Specifications – Victory Series



MINERAL CHIP

Classification:	ASTM F 1700 Class III Solid Vinyl Tile		
Construction:	Multiple color chips scattered throughout homogeneous tile		
Overall Thickness:	.120" / 3 mm (nominal)		
Wearlayer Thickness:	N/A, solid vinyl tile		
Size:	12" x 12", 12" x 18", 18" x 18", 12" x 36", 18" x 36", 36" x 36" plus additional custom sizes		
Edge:	Square, Slight Bevel, Deep Bevel		
Surface Texture:	Frost (FR) <i>recommended</i> , Granite (JS), Slate (SS)		
Standard Colors:	7 colors		
Warranty:	20 years Commercial, Lifetime Residential		
Recycling:	Suitable		
Test Performance:	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good (*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product

STRIA

Classification:	ASTM F 1700 Class III Solid Vinyl Tile		
Construction:	Multiple layers with backing made from 100% pre- and post-consumer materials		
Overall Thickness:	.120" / 3 mm (nominal)		
Wearlayer Thickness:	.032" clear, rigid high density PVC		
Size:	12" x 12", 12" x 18", 18" x 18", 12" x 36", plus additional custom sizes		
Edge:	Square, Slight Bevel		
Surface Texture:	(SR) Stria		
Standard Colors:	8 colors		
Warranty:	20 years Commercial, Lifetime Residential		
Recycling:	Suitable		
Test Performance:	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good (*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product

US SOLIDS

Classification:	ASTM F 1700 Class III Solid Vinyl Tile		
Construction:	Multiple layers with backing which contains pre- and post-consumer materials		
Overall Thickness:	.120" / 3 mm (nominal)		
Wearlayer Thickness:	.032" clear, rigid high density PVC		
Size:	12" x 12", 12" x 18", 18" x 18", 12" x 36", plus additional custom sizes		
Edge:	Square, Slight Bevel		
Surface Texture:	Fresco (FC) <i>recommended</i> , Frost (FR), Pathway (PH), Quarry (QU)		
Standard Colors:	14 colors		
Warranty:	20 years Commercial, Lifetime Residential		
Recycling:	Suitable		
Test Performance:	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good (*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product