

GLUE DOWN

SPECIFICATIONS	GLUE DOWN
Overall Thickness	2.5mm
Wear Layer Thickness	0.5mm (20 mil)
Tile Size	12" x 24"
Plank Sizes (Multi-Width)	5", 6", 7" x 48"
Plank Size	7" x 48"
Urethane	Yes
Edge	MBV
Floor Score®	Yes
Residential Warranty	Lifetime Limited
Heavy Commercial Warranty	10-Year
Tile Packaging (12" x 24")	18 pcs. (36 sq. ft.)
Multi-Width Plank Packaging	18 pcs. (36 sq. ft.)
Plank Packaging (7"x48")	15 pcs. (35 sq. ft.)
Tile Cartons/Pallet (12" x 24")	54
Multi-Width Plank Cartons/Pallet	60
Plank Cartons/Pallet (7"x48")	55
Tile Weight/Carton (12" x 24")	32.63
Multi-Width Plank Weight/Carton	31.77
Plank Weight/Cartons (7"x48")	31.75
ASTM F1700-13 Solid Vinyl Floor Tile	Class III, Type B
ASTM F137-08 Flexibility	Passes
ASTM F386-11 Thickness	Passes
ASTM F410- Wear Layer Thickness	Passes
ASTM F925 Stain and Chemical Resistance (5 minute & 24 hour)	Passes
ASTM F1514 Heat Stability	Passes
ASTM F1515 Light Stability	Passes
ASTM F1914 Immediate & Residual Indentation	Passes
ASTM 2055 Size and Squareness	Passes
ASTM F2199-09 Dimensional Stability	Passes
ASTM D2047 Static COF for Polished Surfaces	Exceeds Industry Standards
ASTM E648-06 Critical Radiant Flux	Class 1
ASTM E662 Smoke Density	Passes

LOOSE LAY

SPECIFICATIONS	LOOSE LAY
Overall Thickness	5.0mm
Wear Layer Thickness	0.5mm (20 mil)
Tile Size	18" x 36"
Plank Size	9" x 59.72"
Urethane	Yes
Edge	MBV
FloorScore®	Yes
Residential Warranty	Lifetime Limited
Heavy Commercial Warranty	10-Year
Tile Packaging (18" x 36")	4 pcs. (18 sq. ft.)
Plank Packaging (9"x 59.72")	6 pcs. (22.4 sq. ft.)
Tile Cartons/Pallet (18" x 36")	52
Plank Cartons/Pallet (9"x 59.72")	60
Tile Weight/Carton (18" x 36")	32.81
Plank Weight/Cartons (9"x 59.72")	40.82
ASTM F1700-13 Solid Vinyl Floor Tile	Class III, Type B
ASTM F137-08 Flexibility	Passes
ASTM F386-11 Thickness	Passes
ASTM F410- Wear Layer Thickness	Passes
ASTM F925 Stain and Chemical Resistance (5 minute & 24 hour)	Passes
ASTM F1514 Heat Stability	Passes
ASTM F1515 Light Stability	Passes
ASTM F1914 Immediate & Residual Indentation	Passes
ASTM 2055 Size and Squareness	Passes
ASTM F2199-09 Dimensional Stability	Passes
ASTM D2047 Static COF for Polished Surfaces	Exceeds Industry Standards
ASTM E648-06 Critical Radiant Flux	Class 1
ASTM E662 Smoke Density	Passes



NovaFloor® commercial is made to the highest environmental standards by Novalis® innovative flooring.

NOVA
FLOOR®
by **NOVALIS** INNOVATIVE FLOORING

Visit us at NovaFloor.us or call 866-NOVALIS

Information in this catalog is subject to change without notice. Color accuracy may vary due to printing. © Novalis 2019